

## FIorentini REGÜLATÖRLER

### FE Serisi Difflü

Kod	Teknik Açıklama	P <sub>in</sub> max (bar)	P <sub>in</sub> out	Çap	Fiyat (EURO)
FE25-L	FE25-L+SSV 25m <sup>3</sup> /h	5-0.3 bar	21-150 mbar	1/2"x1"	110
FE25-L-TR	FE25-L-TR+SSV 25m <sup>3</sup> /h	5-0.3 bar	150-300 mbar	1/2"x1"	120
FES-L	FES-L+SSV 50m <sup>3</sup> /h	5-1 bar	21-150 mbar	1/2"x1"	125
FES-L-TR	FES-L-TR+SSV 50m <sup>3</sup> /h	5-1 bar	150-300 mbar	1/2"x1"	150
FEX1-L	FEX1-L+SSV 75m <sup>3</sup> /h	5-0.4 bar	21-150 mbar	1"x1 1/2"	250
FEX1-L-MP	FEX1-L-MP+SSV 75m <sup>3</sup> /h	5-0.4 bar	150-300 mbar	1"x1 1/2"	260
FEXS-L	FEXS-L+SSV 75m <sup>3</sup> /h	5-0.5 bar	21-150 mbar	1"x1 1/2"	260
FEXS-L-MP	FEXS-L-MP+SSV 75m <sup>3</sup> /h	5-0.5 bar	150-300 mbar	1"x1 1/2"	270



### HP-100 Serisi Difflü Bağlantı

HP 100	HP 100 100kg/h	18-2 bar	0.3-2 bar	1"x1"	160
HP 100/B	HP 100/AP+SSV 100-145m <sup>3</sup> /h	18-1 bar	0.2-0.8 bar	1"x1"	230
HP 100/B TR	HP 100/TR+SSV 100-145m <sup>3</sup> /h	18-2 bar	0.8-4.5 bar	1"x1"	260



### Dival 500 / Serisi Difflü 1"x1"

Kod	Teknik Açıklama	P <sub>in</sub> out	Çap	Fiyat (EURO)
500 BP	DIVAL 500 BP+SSV	9-130 mbar	1"x1"	400
500 MP	DIVAL 500 MP+SSV	90-360 mbar	1"x1"	400
500 TR	DIVAL 500 TR+SSV	290-2100 mbar	1"x1"	525

### Dival 500 / Serisi Difflü 1"x1 1/2"

500 BP	DIVAL 500 BP+SSV	9-130 mbar	1"x1 1/2"	450
500 MP	DIVAL 500 MP+SSV	90-360 mbar	1"x1 1/2"	450
500 TR	DIVAL 500 TR+SSV	290-2100 mbar	1"x1 1/2"	550



### Dival 600 Serisi Flanflı DN40

600BP-40	DIVAL 600 G LBP+SSV	15-130 mbar	DN40 X DN40	1400
600MP-40	DIVAL 600 G LMP+SSV	100-350 mbar	DN40 X DN40	1400
600TR-40	DIVAL 600 G LTR+SSV	300-4100 mbar	DN40 X DN40	1475

### Dival 600 Serisi Flanflı DN50

600BP-50	DIVAL 600 G LBP+SSV	15-130 mbar	DN50 X DN50	1500
600MP-50	DIVAL 600 G LMP+SSV	100-350 mbar	DN50 X DN50	1500
600TR-50	DIVAL 600 G LTR+SSV	300-4100 mbar	DN50 X DN50	1575



### Norval Serisi Flanflı

SN50	NORVAL / GPN16 + SSV	DN50 X DN50	2550
SN80	NORVAL / GPN16 + SSV	DN80 X DN80	2975

## Emniyet Tahliye Vanaları

Tanım	Çap	Bağlantı	Set Aralığı	Fiyat (Euro)
VS/AM 65 BP/MP	25X25	D	15-500 mbar	145
VS/AM 65 TR	25X25	D	500-7000 mbar	165

